

DABO® screw TKR-ZT6-5.5



Application range

- > To secure roofing membrane and insulating material to sheet steel substructures $\geq 3.0 \text{ mm} \leq 6.0 \text{ mm}$
- > For combination with EJOT stress plates and Flat roof profile

Characteristics

- > Case-hardened steel
- > Climadur-coated – high-quality coating to improve corrosion protection (15 Kesternich cycles, DIN 50018, 1997)


Length determination (minimum lengths)

Sheet steel	Insulation thickness + 20 mm
-------------	------------------------------

Applications



Technical specifications



Certifications



Cross references

Stress plate HTV 82/40 F
 Stress plate HTV-40 RU
 Tube washer EcoTek 50
 Flat roof profile FP
 Bit hexalobular TX30

Product online



Order description	Length [mm]	Thread length [mm]	PU [pieces]	Price/100 [EUR]	Article number	EAN
TKR-ZT6-5.5x35*	35	35	500		3495035629	4061245012407
TKR-ZT6-5.5x70*	70	40	500		3495070629	4061245012391
TKR-ZT6-5.5x90*	90	40	500		3495090629	4061245012384
TKR-ZT6-5.5x110*	110	40	250		3495110629	4061245012377

*Production article in case of order (see page 35)

Compatibility acc. to ETA-07/0013

	HTV 82/40	HTE 82/40	HTV 82/40 TK	HTV 82/40 F	HTV 40 RU	HTK 2G 50xL	HTK 2G 75xL	EcoTek 50	EcoTek-T 50	HTK-S	Flat roof profile FP
TKR-ZT6-5.5			X	X				X	X		X